




Dimensions (mm)



Technical Features

Place of Use Indoors, outdoors

Operating Temperature, Humidity -20°C/+68°C (opt. -50°C with heater positive), RH %95 non-condensing.

Operating Intensity %100, 7/24 use.

Built on main carriers and supported with pipe beams on sides, consisting of waterproof and protected top lid with damper for safety. Can be completely disassembled.

A pair of three-section rotors (120°), each having 10+10 (11+11 in optional 2120 mm clear passage height) one by one demountable arms.

Optionally complies with UK H&S regulation of ≤98 mm gap between upright profiles.

Body / Arm Features

Combination options with different material choices:

| | BTC 300 D | BTC 300 D-25 | BTC 300 D-100 |
|-------------|---|--|--|
| Body | Electrostatic powder coating on hot-dip galvanized steel | Electrostatic powder coating on hot-dip galvanized steel | 304 grade (opt. 316 grade)* stainless steel |
| Arms | Electrostatic powder coating on hot-dip galvanized steel, Ø42x2,5 mm. | 304 grade (opt. 316 grade)* stainless steel, Ø40x2,0 mm. | 304 grade (opt. 316 grade)* stainless steel, Ø40x2,0 mm. |

(* Finishing : Satine brushed (opt. electrostatic powder coating on stainless steel).

Indicators / Illumination **Status - Direction Indicators** :   LED, standard/LED passageway illumination standard.

Power **Operating Voltage** : 110/220V AC 50/60 Hz, (%±10), 24V DC.
Consumption : ~16,2W at stand-by, during passage ~7,6+7,6W (varies according to the options and accessories used).

System operates bi-directionally (entry-exit).

Operating Modes Operation modes can be changed through dip switch, IOS and/or android app.
 Entry - exit controlled Entry controlled, exit free Entry free, exit controlled
 Single input both directions use Entry - exit free

Operating System Electromechanical manual operation (opt. electromechanical motorized operation).

Control System

All functions, parameters and operating modes can be changed through the control board (microprocessor controlled), IOS and/or android app. Firmware can be updated. All past function updates and changes are kept in the server and records can be traced.

All inputs are opto-coupler protected.

Controllable by dry contact (ground control).

Compatible with all kinds of access control device.

Optional RS232, RS485 or TCP/IP module is available.



Flow Rate **Passage capacity (manual)** : max. 96 cycle/min. **Nominal** : ~50 pass/min.
Passage capacity (motorized) : max. 80 cycle/min. **Nominal** : ~40 pass/min.
 (nominal passage rate can change depending on the access control system utilized)

Emergency Mode System allows free passage (entry-exit) in both directions (fail safe). Works compatible with fire warning and similar systems. At the end of an emergency situation, system returns to its normal operating mode.

Power-off Situation System allows free passage (entry-exit) in both directions (fail safe). Optionally, can be set (fail secure) as; entry-exit locked, entry free-exit locked, or entry locked-exit free. Free passage in chosen direction by manual override key in fail secure option is available.

Weight ~335 kg

Optional Features and Accessories

Motor driven unit, wireless remote control (receiver-transmitter), manual control, manual override key (with fail secure option), counter (with/without reset), card reader mounting bracket, passage completion sensor, contactless passage sensor (for motorized models), heater positive, canopy, bottom plate (standard or for forklift handling), battery back-up, 316 grade stainless steel, RS232-RS485-TCP/IP modules, limiter, 2120 mm clear passage height, different color choices, compliance with UK H&S regulation of ≤98 mm gap between upright profiles.